

LHD-75 data sheet

The heavy duty torque wrench up to 7500 Nm



Fast. Powerful. Flexible.

- » The new torque wrench, combining power and speed: more than twice as fast as other suppliers – for a faster insertion bolt by bolt
- » Removable, magnetic display with cable length up to 2m
- » Adjustable handles
- » Reliable operation because of a stable voltage supply via power supply unit (Powerbox)
- » Clear and intuitive handling with the help of a LCD-colour display
- » Visual and acoustic zero-defect strategy
- » Torque adjustment in 10 Nm steps
- » Brushless Technology for a longer tool life of the torque wrench
- » Documentation of all bolted connections (Module TRACK optional available)
- » Storable bolting operation assignments (Module QS optional available)
- » Inductive interface for data transmission
- » Repeatability +/- 2 %

Technical Data

Type	~N-m min/ max	~ lbf-ft min/ max	~ U/min	■	Ø D mm	L mm	B mm	H mm	⚖ kg
LHD-75	800 - 7500	590 - 5530	10,3	1½"	102	175	345	497	14.6
Further torque ranges on request.									

Type	Input voltage	Output voltage	P	L mm	B mm	H mm	⚖ kg
Powerbox	180–264 V AC / 47–63 Hz	48 V DC	3.000 W	380	445	160	9.4
Protection: IP32	Protection class I						

